

 Jiangyou Hacer Technology Co., Ltd.

| Steel Grade: Hi-Steel | | | | | | | | |
|-----------------------|----------------------------------|-----------|------------------------------------|-----------|-------------------------------|---------|--------------|------------|
| CHEMICAL COMPOSITION | | | | | | | | |
| C(%) | Si(%) | Mn(%) | Cr(%) ≤ | Ni(%) ≤ | Cu(%) ≤ | Nb(%) ≤ | V(%) | Other(%) ≤ |
| 0.12 | 0.15 | 0.50~1.00 | — | 0.50~1.00 | 0.55~1.30 | — | — | Mo 0.25 |
| MECHANICAL PROPERTIES | | | | | | | | |
| Max Thickness/mm | Yield Strength σ_s /MPa | | Tensile Strength σ_b /MPa | | Extensibility δ ①(%) | | Hardness HBS | |
| 64 | 345 | | 485 | | 24 | | — | |

Remark:

- ①, The distance of testing sample is 50mm(2in) for extensibility, please check the ② if not 50mm.
- ②, The distance of testing sample is 200mm(8in) for extensibility.
- ③, It included commodity grade of low alloy high strength in the United States and Canada.

From: Jiangyou Hacer Technology Co., Limited
 Factory Add: Jiangzhang Road, Jiangyou City, SC, Chir
 Website: <https://www.jhacer.com/>
 Email: sales@jhacer.com
 Phone: +86-(0)816-3260757
 Call:+86-13658128897(WhatsApp)
 Fax: +86-(0)816-3260757